



**Dew point and temperature probe DMP5**

For dew point measurement in high temperatures up to 180 °C

		Probe head and cable	Probe cable	Sensor type	Filter type	Operating pressure	Baud rate	Parity, data bit, stop bit	Probe Modbus address	Reserved	Probe mounting accessory	Connection cable
		<b>DMPX</b>	5	1	A	0				0		
1	<b>Probe head and cable</b> DMP5 for high temperatures	5										
2	<b>Probe cable</b> Probe 5, 2m Probe 5, 10m		A B									
3	<b>Sensor type</b> DrycapS			1								
4	<b>Filter type</b> Sintered stainless steel filter				A							
5	<b>Operating pressure</b> Setting for ppm and other calculated variables 1) <b>1 bar (absolute)</b>					0						
6	<b>Baud rate</b> 1) 19200 9600						A B					
7	<b>Parity, data bit, stop bit</b> 1) 8,N,2 8,E,1 8,O,1							0 2 4				
8	<b>Probe Modbus address</b> 1) 240 110 120 130 140								A B C D E			
9	<b>Reserved</b> None									0		
10	<b>Probe mounting accessory</b> None (installation into existing mounting flange) Mounting flange										0 A	
11	<b>Connection cable</b> None 1,5m, open ends 10m, open ends											0 1 2

1) Factory pre-set, can be changed in the field with a service cable (P/N 242659)

Probe can be connected to INDIGO series of transmitters regardless of the output configuration.

**Selections in bold are included in the prices of the basic versions.**

*Selections in italic are available at an extra price.*

**Example of order code with typical settings:**

<b>For use with INDIGO transmitters</b>	<b>DMPX</b>	<b>5</b>	<b>A</b>	<b>1</b>	<b>A</b>	<b>0</b>	<b>A</b>	<b>0</b>	<b>A</b>	<b>0</b>	<b>A</b>	<b>0</b>
<b>For use with Modbus RTU</b>	<b>DMPX</b>	<b>5</b>	<b>A</b>	<b>1</b>	<b>A</b>	<b>0</b>	<b>A</b>	<b>0</b>	<b>A</b>	<b>0</b>	<b>A</b>	<b>2</b>

Valid from: December 2019